

OCT 19 2007

PATENT
120742**IN THE CLAIMS**

1. (Presently Amended) A work station for an electrical discharge machining apparatus, comprising:

(a) a first mechanism for retaining a workpiece in a predetermined position;

(b) at least one electrode for forming a feature on said workpiece; and,

(c) a second mechanism for positioning said electrode in a manner that is movable into and out of engagement with a designated portion of said workpiece, said second mechanism further comprising:

(1) a stationary first portion including a plurality of shaft members retained in a shaft housing, wherein said shaft members are arranged in a predetermined spaced relation;

(2) a second portion for retaining and positioning said electrode, said second portion including a plurality of openings therein which are slidably positioned on said shaft members; and,

(3) a bearing positioned between a surface defining each said opening in said second portion and each said shaft member, wherein said bearings have electrically insulating properties;

wherein said first [a] portion of said second mechanism is connected to said first mechanism so as to automatically align said electrode with said designated portion of said workpiece.

2. (Original) The work station of claim 1, wherein said second mechanism is configured so that said electrode is electrically insulated from said workpiece.

PATENT
120742

3. (Cancelled)

4. (Presently Amended) The work station of claim 1, [3,] said shaft housing of said first portion for said second mechanism including a male portion configured so as to be retained in a corresponding mating portion provided in said first mechanism.

5. (Original) The work station of claim 4, said shaft housing being configured so that said male portion interfaces with said mating portion of said first mechanism in a direction substantially perpendicular to movement of said second portion of said second mechanism.

6. (Presently Amended) The work station of claim 1, [3,] said first mechanism including an opening configured to retain said shaft housing.

7. (Presently Amended) The work station of claim 1, [3,] said first mechanism including a slot configured to retain said shaft housing.

8. (Presently Amended) The work station of claim 1, [3,] said bearings including a plurality of grooves formed in an inner surface thereof so as to permit fluid flow therethrough.

9. (Presently Amended) The work station of claim 1, [3,] said second portion of said second mechanism further comprising:

(a) a locator plate including a plurality of openings formed therein, each of said openings having one of said bearings positioned therein so that said locator plate is slidably positioned on said shaft members;

(b) a holder plate configured for retaining said electrode in a predetermined position and orientation; and,

(c) at least one clip member for connecting said holder plate to said locator

PATENT
120742

plate.

10. (Original) The work station of claim 9, said holder plate including a plurality of openings formed therein adjacent said electrode to permit fluid flow therethrough.

11. (Original) The work station of claim 10, said second mechanism further comprising a base member positioned adjacent said holder and locator plates, said base member including a plurality of openings formed therein which also receive each said bearing so that said base member is slidable on said shaft members.

12. (Original) The work station of claim 11, said base member including a pocket formed therein in flow communication with said openings in said holder plate.

13. (Original) The work station of claim 1, said second mechanism being oriented with respect to said first mechanism so as to permit said electrode to form a feature in a side portion of said workpiece.

14. (Original) The work station of claim 1, further comprising a third mechanism located on an opposite side of said first mechanism as said second mechanism, said third mechanism positioning a second electrode in a manner that it is movable into and out of engagement with a second designated portion of said workpiece, wherein a portion of said third mechanism is connected to said first mechanism so as to automatically align said second electrode with said second designated portion of said workpiece.

15. (Original) The work station of claim 14, wherein said third mechanism is configured so that said second electrode is electrically insulated from said workpiece.

16. (Presently Amended) A work station for an electrical discharge machining apparatus, comprising: The work station of claim 1,

(a) a first mechanism for retaining a workpiece in a predetermined position, said

PATENT
120742

first mechanism further comprising:

(1) a base portion for supporting said workpiece, said base portion of said first mechanism further comprising:

(i) a first base plate positioned adjacent said housing;

(ii) a second base plate positioned in spaced relation to said first base plate; and,

(iii) at least one spacer member positioned between said first and second base plates;

wherein at least one of said first and second base plates includes a locator member at an end adjacent said second mechanism so as to align said workpiece in a second direction; and,

[(b)] (2) a housing positioned adjacent and connected to said base portion, said housing including at least one locator member for aligning said workpiece in a first direction;

(b) at least one electrode for forming a feature on said workpiece; and,

(c) a second mechanism for positioning said electrode in a manner that is movable into and out of engagement with a designated portion of said workpiece;

wherein a portion of said second mechanism is connected to said first mechanism so as to automatically align said electrode with said designated portion of said workpiece.

17. (Cancelled)

PATENT
120742

18. (Presently Amended) The work station of claim 16, [17,] said first mechanism further comprising at least one spacer member positioned adjacent said housing opposite said first base plate, each spacer member including an arm portion extending beyond said base portion having an opening formed therein which retains a male portion of said second mechanism.

19. (Presently Amended) The work station of claim 1, [3,] said second mechanism including at least two shaft members positioned in spaced, parallel relation to each other.

20. (Presently Amended) The work station of claim 1, [3,] said second mechanism including three shaft members positioned in spaced, substantially triangulated relation to each other.

21. (Presently Amended) An electrical discharge machining apparatus for forming features in a workpiece, comprising:

(a) a dielectric tank;

(b) at least one work station disposed in said tank, each said work station further comprising:

(1) a first mechanism for retaining a workpiece in a predetermined position;

(2) at least one electrode for forming a feature on said workpiece; and,

(3) a second mechanism for positioning said electrode in a manner that it is movable into and out of engagement with a designated portion of said workpiece, said second mechanism further comprising:

(i) a stationary first portion including a plurality of shaft members

PATENT
120742

retained in a shaft housing, wherein said shaft members are arranged in a predetermined spaced relation;

(ii) a second portion for retaining and positioning said electrode, said second portion including a plurality of openings therein which are slidably positioned on said shaft members; and

(iii) a bearing positioned between a surface defining each said opening in said second portion and each said shaft member, wherein said bearings have electrically insulating properties;

wherein a portion of said second mechanism is connected to said first mechanism so as to automatically align said electrode with said designated portion of said workpiece;

(c) a device for supplying power to said electrode; and,

(d) a device for controlling the position of said second mechanism.

22. (Cancelled)